# **ActiveSQX**



## SCALABLE DECODING SOLUTION

Professional AV solutions require video to be received from a great many different sources and locations. The ability to receive and display video directly from online resources such as CCTV networks and remote desktop applications and combining them with local inputs has become an everyday part of a fully functional video wall display.

Datapath's ActiveSQX PCIe plug in card is a powerful addition to systems that require a scalable hardware based decoding solution under a single operation system platform, such as Windows®.

The ActiveSQX includes a dedicated processor capable of decoding several IP streams simultaneously via the on-board ethernet ports.

Fully PCIe compatible, multiple ActiveSQX cards can be used in a single system to provide project scalability, giving users more processing and more simultaneous decodes.

# **DATAPATH SQX TECHNOLOGIES**

Datapath's SQX technology is compatible with industry standards for video compression and streaming.

The ActiveSQX allows users to decode large numbers of High Definition 1080p 60fps streams and multiple ActiveSQX cards reside in a single system to provide even more decoding capabilities.

In addition, the ActiveSQX can be placed in systems alongside graphics cards and video capture cards, such as the Datapath Vision range, to provide a powerful addition to any control room environment.



# Advanced video compression technology

## **COMPATIBILITY**

The ActiveSQX is supported by the following operating systems: Windows 10 64 bit and Windows server 2012.

Datapath SDK is included for software developers.

## **SPECIFICATION**

## **BOARD FORMAT**

PCle x4 gen 2 plug-in card half length, full height

## **CONNECTORS**

2 x RJ45 Ethernet ports, 1 x DisplayPort output connector (reserved for future use)

## **ETHERNET**

Dual 1000 Base-T Ethernet ports DHCP or Static IP support IPv4 & IPv6

## **DMA ENGINE**

Direct DMA to physical or virtual memory buffers with full scatter-gather support DMA bandwidth: up to 1.3GB/s

## **SCALING**

Hardware downscaling prior to DMA transfer. One to One (1:1) transfer for upscale after DMA

#### **CAROUSEL**

IP Window carousel supported including the hardware based pre-buffering of IP decodes for smoother playback

## **STREAMING METHODS**

Multicast & Unicast support

## **STREAMING CODECS**

H.264 (Mpeg4 Part 10 AVC), VC-1, MPEG2 Part 2, MJPEG

#### STREAMING CONTAINERS

MPEG4 part 1, MPEG2-TS, WMV, MOV

## **STREAMING PROTOCOLS**

HTTP, RTSP, RTP, UDP

## **DECODE DENSITY\***

Up to:

1 x 4096 x 2160 at 60fps

3 x 4096 x 2160p at 30fps

6 x 1920 x 1080p at 60fps or 12 x 1080p at 30fps or 10 x 1080i at 30fps/50 D1 at 30fps

## **DE-INTERLACING**

Supported

## **STREAM AUTHENTICATION**

Basic & Digest Stream Authentication

## **VIDEO CAPTURE MEMORY**

4GB

## **H.264 PROFILES**

Constrained Baseline Profile (CBP) / Main Profile (MP) / High Profile (HiP)

## **H.264 LEVELS**

Level 3 / 3.1 / 4 / 4.1 / 4.2 / 5 / 5.1 / 5.2

#### **COLOUR FORMAT**

NV12 4:2:0(MP) / High Profile (HiP)

## **POWER REQUIREMENTS**

Max current at +33 - 19A Max current at +12V-1.9A Average power ≈ 14W

## **OPERATING TEMPERATURE**

0 to 35 °C / 32 to 96 °F

## **STORAGE TEMPERATURE**

-20 to 70 °C / -4 to 158 °F

## **RELATIVE HUMIDITY**

5% to 90% non-condensing

## WARRANTY

3 years

\* Decode density may be affected if either the encoded stream was originally encoded to a pixel format other than NV12 (eg. YV12) or if the encoded stream is interlaced and requires de-interlacing.

# **MODELS AVAILABLE**

Order Code: ActiveSQX Dedicated decoding card

All products are shipped with the latest software available, unless stated otherwise. Special requirements may be organised by contacting our Sales team.

Datapath UK and **Corporate Headquarters** 

Bemrose House, Bemrose Park, Wayzgoose Drive, Derby, DE21 6XQ, United Kingdom

+44 (0) 1332 294 441

sales-uk@datapath.co.uk

**Datapath North America** 2490 General Armistead Avenue. Suite 102, Norristown, PA 19403,

USA

+1 484 679 1553 ☑ sales-us@datapath.co.uk

